





Renew Your World

NIPPON PAINT INTERIOR WALL PRIMER

Nippon Paint Interior Wall Primer is a water based and is formulated to provide good adhesion to the interior masonry and cement surfaces. It has good hiding properties and is easy to apply.



Feature	Action	Benefit
 Acrylic Formula	Strong anchorage to the substrate	Blister free walls for longer
 High solid content	Superior opacity	Better concealment and gives a premium rich top coat finish

Where to use: Can be used on interior walls, ceilings and hard & soft boards.

Technical Data (Specification Data)

Colour Range: White
Finish: Matt
Coverage: 210-230 sq.ft / litre / one coat (Actual coverage is dependant on the substrate condition & surface roughness)
Dry Time: To Touch: 30 minutes To Recoat: 4-6 Hours
Clean Up Solvent: Clean, Potable Water
Stability of diluted paint: 24 Hours
Shelf Life: 2 Years from the date of manufacture in original tightly closed containers. Higher temperature during storage may reduce the shelf life and may lead to gelling in the container.
Dilution: 50 % by volume with clean, Potable water for Interiors

Standard Application System

Surface Preparation:

Clean the surface till it is free from dust, grease and any flaking paint from surface. Apply Interior primer allow to dry for 4-6 hrs. Apply Nippon Acrylic Wall putty for smoothening out dents. Allow to dry putty thoroughly apply one more coat of Interior primer on puttied surface. Allow painted surface to dry for 4-6hrs. before applying top coat.

Recommended Paint System

Sequence	Product	No. of Coats
Primer	Nippon Interior Primer	Apply 1 coat and allow to dry for 4 - 6 hours
Putty	Nippon Acrylic Wall Putty	Apply Nippon Acrylic Wall Putty 1-2 coats for smoothening of surface. Allow to dry overnight.
Primer	Nippon Interior Primer	Apply 1 coat and allow to dry for 4 - 6 hours
Topcoat	Nippon Interior Emulsion Paint	Apply 2-3 coats at an interval of 4-6 hrs

Precautions

Avoid painting when the temperature is below 10 degrees Celsius. Painting is not recommended if the moisture content and alkalinity of the walls is high. Moisture content of the walls should be below 16% (measured by Protimeter) and alkalinity of the wall should be below pH-9. Relative humidity should be below 85%. Painting on a newly plastered wall is recommended after 12 weeks of curing.

Application

Brush:	Dilute with water 50% for interior use
Roller:	Dilute with water 50% for interior use
Conventional Spray:	Dilute with water 30% - 40% for interior use

Safety health & Environmental information

During Painting	Always work in a well ventilated area. Wear appropriate attire, especially gloves and eye protection gear. Avoid contact with skin as it may cause irritation.
Cleaning	Wash all the tools with water immediately after application.
Safety instructions	In the case of eye contact, rinse immediately with water and seek immediate medical treatment. To remove paint for skin, use soap and water or appropriate cleanser. In the event of spillage, contain and collect spilt paint by using sand or earth.
Storage	Store paint in a cool, dry and well ventilated place away from heat sources, flammables or direct sunlight. Keep container tightly closed in a secure, upright position. Do not store near food, drink or animal feed. Keep out of reach of children. Do not dispose of unwanted paint into drains, water sources or open sewers. To dispose safely, pour unwanted paint onto old newspapers and let dry before placing in a proper waste receptacle
Environment	Does not contain any added lead, mercury or chromium compounds.