



## MULTI-PURPOSE WALL SEALER

NIPPON MULTI-PURPOSE water based wall sealer is specially formulated to provide excellent adhesion and wall sealing. This product is suitable for both interior and exterior, masonry and gypsum surfaces. It bonds well with cement and plastered surfaces, thus enhancing the life of top coat. It has superior anti-algal and anti-fungal properties.



Feature	Action	Benefit
High Emulsion Content	Higher Coverage	Better performance with low cost per sq.ft.
2 X Solid content	Superior Opacity	More hiding & gives premium rich top coat finish
Anti-fungal	Resists algae & fungal attack	Ensure long lasting performance

### Technical Data (Specification Data)

Colours	White	
Finish	Matt	
Coverage	12 - 14 m <sup>2</sup> / litre / coat (Actual coverage is dependant on the substrate condition)	
Dry Time 77°F (25°C) & 50 RH	To touch: 30 minutes	To re-coat: 4 - 5 hours
Dilution	100% by volume with clean, potable water for exteriors 50% by volume with clean, potable water for interiors	

NIPPON PAINT (INDIA) PRIVATE LIMITED, 9th Floor, East Wing, KRM Centre, No.2, Harrington Road, Chetpet, Chennai - 600 031, Tamil Nadu, India. Ph: 044 - 42982222, Fax : 044 - 42982200, Email: [tu@nipponpaint.co.in](mailto:tu@nipponpaint.co.in), Toll-free No: 1800-425-3636, SMS 'NIPPON' at 53636

### Standard Application System

Surface preparation	Remove flakes of old paint or powdery residues by sanding using an emery paper. Surface must be free from dirt, grease, oil and other foreign substances. Algae and fungus on walls to be removed by high pressure water wash or coil brush and apply Nippon Bio-Wash fungicidal solution. Fill cracks and allow the surface to dry completely before painting.
---------------------	---

### Recommended Paint System

Directions for use	Apply a coat of Multipurpose primer with 50%-100% dilution depending upon the type of the surface. Allow to dry for 4-5 hrs. Do not keep unpainted more than 15 days. Immediately apply a 2-3 coats of Nippon Exterior emulsion paint.
--------------------	--

### Precautions

Avoid painting when the temperature is below 10 degrees Celsius. Painting is not recommended if the moisture content and alkalinity of the walls is high. Moisture content of the walls should be below 16% (measured by Protimeter) and alkalinity of the wall should be below pH-9. Relative humidity should be below 85%. Painting on a newly plastered wall is recommended after 12 weeks of curing.

### Application

Brush	Dilute with water 50% for interior use and 100% for exterior use
Conventional spray	Dilute the paint with 30% water
Airless Spray	Dilute with 10%-15% water

### Safety, Health & Environmental Information

During painting	Always work in a well ventilated area. Wear appropriate attire, especially gloves and eye protection gear. Avoid contact with skin as it may cause irritation.
Cleaning	Clean the equipment with water immediately after use
Safety instructions	In the case of eye contact, rise immediately with water and seek immediate medical treatment. In the event of spillage, contain and collect spill paint by using sand on earth. Remove splashes of paint from skin by using soap and water.
Storage	Store paint in a cool, dry and place them away from heat sources, flammables or direct sunlight. Keep container tightly closed in a secure, upright position. Do not store near food, drink or animal feed. Keep out of reach of children. Dispose paint waste in accordance with the prevalent environmental quality regulation.
Environment	Does not contain any added lead, mercury or chromium compounds.

NIPPON PAINT (INDIA) PRIVATE LIMITED, 9th Floor, East Wing, KRM Centre, No.2, Harrington Road, Chetpet, Chennai - 600 031, Tamil Nadu, India. Ph: 044 - 42982222, Fax : 044 - 42982200, Email: [tu@nipponpaint.co.in](mailto:tu@nipponpaint.co.in), Toll-free No: 1800-425-3636, SMS 'NIPPON' at 53636