

 **NIPPON
PAINT**
Inspired by you

WEATHERBOND PRO

HIGH DURABLE EXTERIOR EMULSION

Double Layer Technology



TO PAINT YOUR HOME WITH NIPPON PAINT, CALL: 1800 425 3636

WEATHERBOND PRO

HIGH DURABLE EXTERIOR EMULSION



Nippon Paint Weatherbond PRO is a high performance, pure acrylic exterior painting system which offers outstanding protection for exterior surfaces. The product also offers unique protection against water, algal attack, dust pick-up, hairline crack bridging, efflorescence and extreme weather. Weatherbond PRO system provides effective waterproofing and anti-carbonation properties.



*on tested conditions

Feature	Action	Benefit
Appearance	Rich sheen, accent shades	Rich appearance
Dirt Pick Up Resistant	It doesn't allow dirt/dust to settle on walls	Therefore the exteriors look new and beautiful for years
Water Resistant Film	It is specially formulated to be resistant to water and other climatic changes	No damp and shabby surfaces
Low VOC	It does not emit air polluting harmful vapours and paint odour that pollutes the environment	Environment friendly and Healthy paint
Algal and Fungal Resistance	It is specially formulated to be resistant to the elements such as fungus, algae, chalking and flaking	Gives a polished look to your home for years to come
Extreme Durability	Best Bio-pack system, resistance to water and anti-fading formula	Surface and colours look uniform giving a beautiful look to the walls for years

WARRANTY:

Performance warranty up to 15 years* (Color Retention and Film Integrity) for both the basecoat and topcoat products on vertical walls when applied as a system.

10* years waterproofing warranty and 10* years Anti-algal warranty for vertical walls when applied as a system.



COVERAGE:

Weatherbond PRO Emulsion: 55 - 65 ft²/litre for 2 coats

Weatherbond PRO Base coat: Maximum Coverage of 30-35 ft²/litre per coat for both Repainting as well as fresh concrete.

FINISH: Sheen finish

STANDARD APPLICATION SYSTEM

SURFACE PREPARATION:

For Repainting: Clean the surface till it is free from dust, grease and flaking paint. Any unstable paint to be removed, using high pressure wash or scraper whichever is appropriate. Algae and Fungus on the wall to be removed, by using high pressure wash or coir brush and shall be treated with Walltron Kleanwall Fungicidal solution.

New plaster/Fresh Concrete: Ensure surface is completely cured and dry. Application of cement paint/lime/cement putty as undercoat is not recommended. Fill the cracks upto 3mm if any with Walltron N-seal cracksealer powder.

***Warranty:** Please refer the warranty card for further details

Post application instruction: To enhance the performance of paint film, clean the exterior surface, algae or fungus if any with clean water in an interval of 6 months.

RECOMMENDED PAINTING SYSTEM:

FOR FRESH CONCRETE

Sequence	Product	No. of coats
Primer	DR. Bond Efflorescence Resistant sealer	Apply a coat with 100% dilution using potable water by volume. Allow it to dry for 4-6 hours
Base Coat	Weatherbond PRO Basecoat	Apply a coat with 30% dilution using potable water by volume
Base Coat	Weatherbond PRO Basecoat	Apply a coat without dilution
Top Coat	Weatherbond PRO Emulsion	2-3 coats with upto 20% dilution with potable water by volume at an interval of 4-6 hours

FOR REPAINTING

Sequence	Product	No. of coats
Primer	DR. Bond Efflorescence Resistant sealer	Apply a coat with 100% dilution using potable water by volume. Allow it to dry for 4-6 hours
Base Coat	Weatherbond PRO Basecoat	Apply a coat without dilution
Top Coat	Weatherbond PRO Emulsion	2-3 coats with upto 20% dilution with potable water by volume at an interval of 4-6 hours

Note: For dark shades & Horizontal surfaces 1 or 2 additional coats may be required for better performance of paint film. The primed surface should be immediately painted with subsequent coats.

Note: Weatherbond PRO should not be applied on surfaces/substrates that are subjected to continuous seepage or dampness.



**Colour
Protection**



**Weather
Protection**



**Dirt
Protection**



CORPORATE OFFICE

NIPPON PAINT (INDIA) PRIVATE LIMITED

No. 3, Club House Road, 3rd Floor, Chennai - 600 002, Tamil Nadu, India. Tel: 044 4298 2222, Fax: 044 4298 2200

Email: tu@nipponpaint.co.in | SMS NIPPON to 53636 | Toll-free: 1800 425 3636

www.nipponpaint.co.in