



NIPPON PAINT MAXX DURAFRESH

Nippon MAXX Durafresh is a specially formulated high performance exterior emulsion paint with heat ban technology and silicon ideally suited for tropical weather conditions. It imparts a sheen finish and provides better anchoring and water resistant. It has anti-algal and dirt pick resistance to keep your walls fresh for longer time.

GREEN ASSURED



PRODUCT FEATURES



Dirt Pick-up Resistant

The exteriors look new and beautiful for years.



Water Resistant

Resulting in no blistering and peeling of the paint film.



Heat Ban Technology

This makes the interior cooler, thus helping to save energy used for air conditioning.



Ultra Low VOC

Environment friendly and Healthy paint



TECHNICAL DETAILS

Bases	:	White & Bases
Colour Range	:	Please refer to Nippon Paint shade card and fan decks
Finish	:	Sheen finish
Dry Time	:	To Touch: 30 minutes To Recoat: 4-6 hours
Gloss level	:	60° head: 5 -15
Clean up solvent	:	Clean, potable water
Stability of diluted paint	:	24 Hours
Shelf life	:	3 Years from the date of manufacture in original tightly closed containers
Dilution System A	:	upto 50% by volume with clean, potable water.

Coverage:



MAXX DURAFRESH

110 - 130 sq.ft./litre/coat &
55 - 65 sq.ft./litre/2 coats

(Actual coverage is dependent on the substrate condition, surface porosity, method of application)


HOW TO APPLY

Surface Preparation:

For Repainting: Clean the surface till it is free from dust, grease and flaking paint. Any unstable paint to be removed, using high-pressure wash or scraper, whichever is appropriate. Algae and fungus on the wall to be removed, by using high-pressure wash or coir brush and shall be treated with Walltron Kleanwall Fungicidal solution.


New plaster/Fresh Concrete: Ensure surface is completely cured and dry. Application of cement paint/lime/Cement putty as undercoat is not recommended. Fill the cracks up to 3mm if any with Walltron N-seal cracksealer powder.

Recommended Painting System:



Primer
Nippon Dr. Bond Efflorescence Resistance Sealer/
Nippon Paint Multi-Purpose Wall Sealer/MAXX Exterior Primer

Apply 1 coat



Top Coat
Nippon Paint
MAXX Durafresh

Apply 2-3 coats

Application:

MAXX Durafresh can be applied using Brush, Roller or Conventional Spray.



Allow it to dry for 4-6 hours

Note: For dark shades and Horizontal surface, one or two additional coats are recommended for better performance of paint film. Primed surface should be immediately painted with top coats. For best Performance use Nippon Dr. Bond Efflorescence Resistance Sealer as primer.

SAFETY AND ENVIRONMENT

During Painting:

Always work in a well ventilated area. Wear appropriate attire, especially gloves and eye protection gear. Avoid contact with skin as it may cause irritation.

Cleaning:

Clean all equipments with clean water immediately after use.

Safety Instructions:

In the case of eye contact, rinse immediately with water and seek immediate medical treatment. To remove paint from skin, use soap and water or appropriate cleanser. In the event of spillage, contain and collect spilt paint by using sand or earth.

Precautions:

Avoid painting when the temperature is below 10°C. Painting is not recommended if the moisture content and alkalinity of the walls is high. Moisture content of the walls should be below 16% (measured by Protimeter) and alkalinity of the wall should be below pH-9. Relative humidity should be below 85%. Painting on a newly plastered wall is recommended after 12 weeks of curing.

Post Application Instruction : To enhance performance of the paint film , clean the exterior surfaces, algae or fungus if any with clean water in an interval of 6 months.

Storage:

Store paint in a cool, dry and well ventilated place away from heat sources, flammables or direct sunlight. Keep container tightly closed in a secure, upright position. Do not store near food, drink or animal feed. Keep out of reach of children. Do not dispose of unwanted paint into drains, water sources or open sewers. To dispose safely, pour unwanted paint onto old newspapers and let dry before placing in a proper waste receptacle.

Disposal Information:

Disposal of any paint waste & containers in accordance with applicable Environment (Protection) Act 1986 under the Hazardous Wastes (Management & Handling) rules 1989.

Environment:

Does not contain any added lead, mercury or chromium Compounds.
Lead content does not exceed 90 parts per million.

