



## NIPPON PAINT MAXX INTERIOR PRIMER

MAXX Interior Primer is water based and is formulated to provide good adhesion to interior masonry and cement surfaces. It has good hiding properties and is easy to apply.

## GREEN ASSURED



## PRODUCT FEATURES



### Low VOC

Healthy interiors – ensures that home owners can occupy the house immediately after painting



## TECHNICAL DETAILS

Bases	:	White
Colour Range	:	Please refer to Nippon Paint shade card and fan decks
Finish	:	Smooth Matt
Dry Time	:	To Touch: 30 minutes      To Recoat: 4-6 Hours
Gloss level	:	60° Head: 0 to 5 units
Clean up solvent	:	Clean, potable water
Stability of diluted paint	:	24 Hours
Shelf life	:	3 Years from the date of manufacture in original tightly closed containers .
Dilution	:	upto 50% by volume with clean, potable water

## Coverage:



### MAXX INTERIOR PRIMER

180-200 sq ft/litre/coat

(Actual coverage is dependant on the substrate condition, surface porosity, method of application)

## HOW TO APPLY

### Surface Preparation:




Clean the surface till it is free from dust, grease and any flaking paint from surface. Apply Latex Interior primer allow to dry for 4-6 hrs. Apply Nippon Acrylic wall putty for smoothening out dents. Allow to dry putty thoroughly apply one more coat of Latex Interior primer on puttied surface an allow painted surface to dry for 4-6hrs, before applying top coat.


### Application:

Brush:	Dilute with water upto 50% for interior use
Roller:	Dilute with water upto 50% for interior use
Conventional Spray:	Dilute with water upto 50% for interior use


### Process:




**Primer**  
Nippon Paint  
MAXX Interior  
Primer



**Putty**  
Nippon Paint  
Acrylic Wall Putty



**Primer**  
Nippon Paint  
MAXX Interior  
Primer



**Top Coat**  
Nippon Paint  
MAXX Interior  
Emulsion  
Topcoats



Apply 1 coats



Allow it to dry  
for 6-8 hours

Apply 1-2 coats

Allow it to dry  
for 12-18 hours

Apply 1 coats

Allow it to dry  
for 6-8 hours

Apply 2-3 coats

Allow it to dry  
for 4-6 hours

## SAFETY AND ENVIRONMENT

### During Painting:

Always work in a well ventilated area. Wear appropriate attire, especially gloves and eye protection gear. Avoid contact with skin as it may cause irritation.

### Cleaning:

Clean all equipments with clean water immediately after use.

### Safety Instructions:

In the case of eye contact, rinse immediately with water and seek immediate medical treatment. To remove paint from skin, use soap and water or appropriate cleanser. In the event of spillage, contain and collect spilt paint by using sand or earth.

### Precautions:

Avoid painting when the temperature is below 10 degrees Celsius. Painting is not recommended if the moisture content and alkalinity of the walls is high. Moisture content of the walls should be below 16% (measured by Protimeter) and alkalinity of the wall should be below pH-9. Relative humidity should be below 85%. Painting on a newly plastered wall is recommended after 12 weeks of curing.

### Storage:

Store paint in a cool, dry and well ventilated place away from heat sources, flammables or direct sunlight. Keep container tightly closed in a secure, upright position. Do not store near food, drink or animal feed. Keep out of reach of children. Do not dispose of unwanted paint into drains, water sources or open sewers. To dispose safely, pour unwanted paint onto old newspapers and let dry before placing in a proper waste receptacle.

### Disposal Information:

Disposal of any paint waste & containers in accordance with applicable Environment (Protection) Act 1986 under the Hazardous Wastes (Management & Handling) rules 1989.

### Environment:

Does not contain any added lead, mercury or chromium compounds. Lead content does not exceed 90 parts per million.

